

Compact Industrial Router

4G/5G IoT Industrial Gigabit Router

SMANEX SR403G/ SR503G is a high-performance 4G/5G gigabit router designed for industrial applications. With its compact design, it features a rugged enclosure and accessories that can be mounted on a wall. The router offers dual SIM functionality, 2x Gigabit Ethernet ports, VPN capability, and pre-installed software. The SMANEX Gigabit Router can be utilized in various IoT applications, such as Environmental Monitoring, Intelligent Transportation, Industrial Automation, Surveillance, Smart City, etc.



Hardware Spec

Interfaces	Ethernet	1*WAN/ 2*LAN, 3*LAN 10/100/1000 Mbps
	Serial Port	2*RS232, 2*RS485
	SIM	2
	WiFi	IEEE802.11a/b/g/n/ac
	Antenna	4G: SMA*2 WiFi: SMA*4
Power	Power Input	12---48VDC
	Consumption (operation)	350mA@12VDC (3/4G)
	Consumption (stand-by)	260mA@12VDC
Ambient Temperature	Relative Humidity	≤ 95% (no condensation)
	Operating Temperature	-40 ~ +75°C
	Storage Temperature	-40 ~ +85°C
Certificate	CE/RoHS	

FEATURES

Compact Industrial Router

Software Spec

Network	Connectivity	LTE-FDD: B1/3/5/7/8/20/28 LTE-TDD: B38/B40/B41 WCDMA: B1/ B5/ B8/ GSM: B3/B8
	WAN	Static IP, DHCP, PPPoE
Protocols	IP Routing	Static Router, RIP, OSPF (optional)
	DDNS	DYDNS, CHANGEIP, 88ip, 3322
Security	Firewall	NAT, PAT, DMZ, Port Forwarding, Virtual Server
	VPN	IPSec VPN, L2TP, PPTP, GRE, OPENVPN
Reliability	Redundancy	Dual SIM
	Link On-line Detection	Keep Session
		ICMP, Internet Control Message Protocol
Embedded Watch Dog	Hardware Watch Dog	
Management	Configuration	Local or Remote MQTT, HTTP, HTTPS, Telnet, SSH
		Parameter Backup and Recovery
		SNMP v1/v2/v3
		Configuration via Cloud Platform
	Upgrade	Local upgrade
		Remote upgrade via WEB/TFTP/FTP
		Upgrade via cloud server
	Log Management	Local and remote log management
	Reboot	Remote reboot with scheduling
	PING	Internet diagnosis

FEATURES